CLAIMS

1	1. A computer implemented method for rolling back a
2	system state after a modification failure, the method
3	comprising the steps of:
4	a rollback manager creating a restore point on a
5	computer;
6	the rollback manager storing a reboot indicator
7	in non-revertible storage;
8	the rollback manager monitoring the reboot
9	indicator to detect an unexpected reboot
10	during deployment of a modification; and
11	the rollback manager configuring the computer
12	responsive to the reboot indicator.
1	2. The method of claim 1 wherein the rollback manager
2	configuring the computer responsive to the reboot indicator
3	further comprises:
4	responsive to the reboot indicator indicating
5	that at least one unexpected reboot occurred
6	during the deployment of the modification,
7	the rollback manager rolling back the system
8	state of the computer according to the
9	restore point.

- 1 3. The method of claim 1 wherein the rollback manager 2 creating a restore point on a computer further comprises: 3 the rollback manager auditing the computer and storing in non-revertible storage information concerning at least one item 5 from a group of items consisting of: 6 7 at least one currently executing system 8 process; 9 at least one currently executing user 10 process; and at least one currently open listening port. 11
- 1 4. The method of claim 3 wherein the rollback manager
 2 configuring the computer responsive to the reboot indicator
 3 further comprises:
- responsive to the reboot indicator indicating 4 5 that no unexpected reboots occurred during the deployment of the modification, the 6 7 rollback manager re-auditing the computer, 8 and comparing re-audit information to the 9 stored audit information; and 10 the rollback manager performing an appropriate 11 action responsive to results of the 12 comparison.

1 5. The method of claim 4 wherein the rollback manager 2 performing an appropriate action responsive to the 3 comparison further comprises: 4 responsive to the comparison revealing that at 5 least one item from the initial audit is no 6 longer present on the computer, the rollback 7 manager rolling back the system state of the 8 computer according to the restore point. The method of claim 4 wherein the rollback manager 1 2 performing an appropriate action responsive to the 3 comparison further comprises: 4 responsive to the comparison revealing that all 5 items from the initial audit are still 6 present on the computer, the rollback 7 manager deeming the computer stable. 1 The method of claim 6 wherein the rollback manager 7.

1 8. The method of claim 6 further comprising:

indicator.

deeming the computer stable further comprises:

2

3

4

the rollback manager clearing the reboot

2 the rollback manager deploying rollback 3 capability on the computer; and the rollback manager storing, in non-revertible 5 storage, information concerning deployment of the rollback capability on the computer; 7 wherein the rollback manager deeming the 8 computer stable further comprises the 9 rollback manager disabling the deployed 10 rollback capability. 1

9. The method of claim 4 further comprising:

the rollback manager waiting for a specified

period of time before re-auditing the

computer, and comparing re-audit information

to the stored audit information.

2

3

5

1 10. The method of claim 4 further comprising: 2 the rollback manager repeating the following 3 steps a specified number of times at specified intervals: 5 responsive to the reboot indicator 6 indicating that no unexpected reboots 7 occurred during the deployment of the 8 modification, the rollback manager re-9 auditing the computer, and comparing

10	re-audit information to the stored
11	audit information; and
12	the rollback manager performing an
13	appropriate action responsive to
14	results of the comparison.
1	11. The method of claim 1 further comprising:
2	the rollback manager configuring the reboot
3	indicator to indicate that a modification is
4	to be deployed.
1	12. The method of claim 11 further comprising:
2	the rollback manager configuring the reboot
3	indicator to indicate that the deployment of
4	the modification is expected to reboot the
5	computer.
1	13. The method of claim 12 wherein the rollback
2	manager configuring the reboot indicator to indicate that
3	the deployment of the modification is expected to reboot
4	the computer further comprises:
5	the rollback manager monitoring deployment of the
6	modification; and

7	the rollback manager configuring the reboot
8	indicator responsive to the deployment
9	requesting a reboot of the computer.
1	14. The method of claim 1 wherein the rollback
2	manager monitoring the reboot indicator to detect an
3	unexpected reboot during deployment of a modification
4	further comprises:
5	the rollback manager reading the reboot indicator
6	after a reboot of the computer, before the
7	booting of an operating system;
8	the rollback manager determining, based on the
9	reboot indicator, whether the reboot was
10	legitimate.
1	15. The method of claim 14 further comprising:
2	the rollback manager updating the reboot
3	indicator to indicate the occurrence of the
4	reboot.
1	16. The method of claim 14 further comprising:
2	responsive to determining that the reboot was not
3	legitimate, the rollback manager rolling
4	back the system state of the computer

according to the restore point.

1	17.	The method of claim 1 wherein the reboot
2	indicator	comprises at least one attribute from a group of
3	attributes	s consisting of:
4		an indication of whether a reboot is expected;
5		an indication of a specific number of reboots
6		that are expected;
7		a counter of executed reboots; and
8		an indication of whether a modification is being
9		deployed.
1	18.	The method of claim 1 further comprising:
2		the rollback manager deploying rollback
3		capability on the computer; and
4		the rollback manager storing, in non-revertible
5		storage, information concerning deployment
6		of the rollback capability on the computer.
1	19.	The method of claim 18 wherein the rollback
2	manager co	onfiguring the computer responsive to the reboot
3	indicator	further comprises:
4		the rollback manager rolling back the system
5		state of the computer according to the

restore point; and

,	the foliback manager disabiling the deproyed
8	rollback capability.
1	20. A computer readable medium containing a computer
2	program product for rolling back a system state after a
3	modification failure, the computer program product
4	comprising:
5	program code for creating a restore point on a
6	computer;
7	program code for storing a reboot indicator in
8	non-revertible storage;
9	program code for monitoring the reboot indicator
10	to detect an unexpected reboot during
11	deployment of a modification; and
12	program code for configuring the computer
13	responsive to the reboot indicator.
1	21. The computer readable medium of claim 20 further
2	comprising:
3	program code for, responsive to the reboot
4	indicator indicating that at least one
5	unexpected reboot occurred during the
6	deployment of the modification, rolling back
7	the system state of the computer according

to the restore point.

1	22.	The computer readable medium of claim 20 further
2	comprisin	g:
3		program code for auditing the computer and
4		storing in non-revertible storage
5		information concerning at least one item
6		from a group of items consisting of:
7		at least one currently executing system
8		process;
9		at least one currently executing user
10		process; and
11		at least one currently open listening port.
1	23.	The computer readable medium of claim 22 further
2	comprisin	g:
3		program code for, responsive to the reboot
4		indicator indicating that no unexpected
5		reboots occurred during the deployment of
6		the modification, re-auditing the computer,
7		and comparing re-audit information to the
8		stored audit information; and
9		program code for performing an appropriate action
10		responsive to results of the comparison.

1 24. The computer readable medium of claim 23 further 2 comprising: 3 program code for, responsive to the comparison 4 revealing that at least one item from the 5 initial audit is no longer present on the 6 computer, rolling back the system state of 7 the computer according to the restore point. 1 25. The computer readable medium of claim 23 further 2 comprising: 3 program code for, responsive to the comparison 4 revealing that all items from the initial 5 audit are still present on the computer, 6 deeming the computer stable. 1 26. A computer system for rolling back a system state 2 after a modification failure, the computer system 3 comprising: 4 a creation module, configured to create a restore 5 point on a computer; 6 a storage module, configured to store a reboot

to the creation module;

indicator in non-revertible storage, the

storage module being communicatively coupled

7

8

a monitoring module, configured to monitor the reboot indicator to detect an unexpected reboot during deployment of a modification, the monitoring module being communicatively coupled to the storage module; and a computer configuration module, configured to configure the computer responsive to input from the monitoring module concerning the reboot indicator, the computer configuration module being communicatively coupled to the monitoring module.

27. The computer system of claim 26 further

2 comprising:

a rollback module, configured to roll back the
system state of the computer according to
the restore point, responsive to input from
the monitoring module indicating that at
least one unexpected reboot occurred during
the deployment of the modification, the
rollback module being communicatively
coupled to monitoring module and to the
computer configuration module.

1	28.	The computer system of claim 26 further
2	comprisin	g:
3		an auditing module, configured to audit the
4		computer, the auditing module being
5		communicatively coupled to monitoring module
6		and to the storage module; wherein
7		the storage module is further configured to
8		store, in non-revertible storage,
9		information concerning at least one item
10		from a group of items consisting of:
11		at least one currently executing system
12		process;
13		at least one currently executing user
14		process; and
15		at least one currently open listening port.
1	29.	The computer system of claim 28 wherein:
2		the auditing module is further configured to re-
3		audit the computer, responsive to input from
4		the monitoring module indicating that no
5		unexpected reboots occurred during the
6		deployment of the modification; the computer
7		system further comprising

8	a comparison module, configured to compare re-
9	audit information to the stored audit
10	information, the comparison module being
11	communicatively coupled to the auditing
12	module and to the computer configuration
13	module; wherein
14	the computer configuration module is further
15	configured to perform an appropriate action
16	responsive to input from the comparison
17	module.
1	30. The computer system of claim 29 wherein:
2	the rollback module is further configured to roll
3	back the system state of the computer
4	according to the restore point, responsive
5	to input from the comparison module
6	indicating that at least one item from the
7	initial audit is no longer present on the
8	computer, wherein the rollback module is
9	communicatively coupled to the comparison

1 31. The computer system of claim 29 further

module.

2 comprising:

3	a stability deeming module, configured to deem
4	the computer stable, responsive to input
5	from the comparison module indicating that
6	all items from the initial audit are still
7	present on the computer, the stability
8	deeming module being communicatively coupled
9	to the comparison module.

A computer implemented method for auditing a 1 2 computer system state, the method comprising the steps of: 3 a rollback manager auditing the computer and storing in non-revertible storage information concerning at least one item 5 from a group of items consisting of: 6 at least one currently executing system 7 8 process; at least one currently executing user 9 10 process; and

11

at least one currently open listening port.